

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2021/0108549 A1 ITO et al.

Apr. 15, 2021 (43) **Pub. Date:**

(54) CONTROL DEVICE CONTROLLING CO2 RECOVERY DEVICE

(71) Applicant: TOYOTA JIDOSHA KABUSHIKI

KAISHA, Toyota-shi (JP)

(72) Inventors: Masaki ITO, Toyota-shi (JP); Sakiko

YOSHIDA, Mishima-shi (JP); Hiroki MURATA, Gotemba-shi (JP);

Kazumasa OKAMURA, Gotemba-shi (JP); Toshihiro NAKAMURA,

Sunto-gun (JP); Kohei WATANABE,

Susono-shi (JP)

(73) Assignee: TOYOTA JIDOSHA KABUSHIKI

KAISHA, Toyota-shi (JP)

(21) Appl. No.: 17/024,321

(22)Filed: Sep. 17, 2020

(30)Foreign Application Priority Data

Oct. 9, 2019 (JP) 2019-186114

Publication Classification

(51) Int. Cl.

F01N 9/00 (2006.01)B60R 16/033 (2006.01) F01N 3/08 (2006.01)F01N 3/02 (2006.01)B01D 53/02 (2006.01)B01D 53/14 (2006.01)

(52) U.S. Cl.

CPC F01N 9/00 (2013.01); B60R 16/033 (2013.01); F01N 3/0857 (2013.01); F01N 3/0871 (2013.01); F25J 3/067 (2013.01); B01D 53/02 (2013.01); B01D 53/14 (2013.01); F01N 2900/08 (2013.01); F01N 3/0205 (2013.01)

(57)**ABSTRACT**

A vehicle includes a battery and a CO₂ recovery device using electric power of the battery to recover CO2 contained in inflowing gas. A control device mounted in the vehicle controls the CO2 recovery device. The control device permits operation of the CO₂ recovery device in the case where a high efficiency recovery condition, at which it is predicted that the efficiency of recovery of CO₂, showing a ratio of the amount of recovery of CO₂ in the CO₂ recovery device with respect to the electric power consumed by the battery, will become equal to or greater than a preset predetermined efficiency, is satisfied, and prohibits operation of the CO₂ recovery device in the case where the high efficiency recovery condition is not satisfied.

